

	Asplit® VEQ Powder
Revision date: 07.08.2018	· ·
Revision date: 07.00.2010	Product code: 00359-1203 Page 1 of a
SECTION 1: Identification	on of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Asplit® VEQ Powde ArtNo.	r
592 0360	
	es of the substance or mixture and uses advised against
Use of the substance/n filler	nixture
1.3. Details of the supplier	of the sefety data shoot
Company name:	TIP TOP Oberflaechenschutz Elbe GmbH
Street:	Heuweg 4
Place:	D-06886 Wittenberg
Telephone: Responsible Departmer	+49(0)3491/635-50 Telefax: +49(0)3491/635-552 nt: Responsible for the safety data sheet: sds@gbk-ingelheim.de
1.4. Emergency telephone	
number:	In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111
SECTION 2: Hazards ide	•
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements	2/2008 n toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled.
Hazard categories: Specific target organ Hazard Statements: May cause damage <u>2.2. Label elements</u> Regulation (EC) No. 1272	2/2008 n toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements	2/2008 n toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo	2/2008 n toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz	2/2008 n toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008 r labelling
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz Signal word: Pictograms: Hazard statements	2/2008 In toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008 r labelling Warning
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz Signal word: Pictograms:	2/2008 n toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008 r labelling
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz Signal word: Pictograms: Hazard statements H373 Precautionary stateme	2/2008 In toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008 r labelling Warning Warning May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.
Regulation (EC) No. 1272 Hazard categories: Specific target organ Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz Signal word: Pictograms: Hazard statements H373	2/2008 In toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008 r labelling Warning Warning May cause damage to organs (lung) through prolonged or repeated exposure if inhaled. nts Do not breathe dust.
Regulation (EC) No. 1272 Hazard categories: Specific target organ Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz Signal word: Pictograms: Hazard statements H373 Precautionary stateme P260	2/2008 In toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008 r labelling Warning Warning May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.
Regulation (EC) No. 1272 Hazard categories: Specific target organ Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz Signal word: Pictograms: Hazard statements H373 Precautionary stateme P260 P285	2/2008 In toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. 2/2008 r labelling Warning Warning May cause damage to organs (lung) through prolonged or repeated exposure if inhaled. nts Do not breathe dust. In case of inadequate ventilation wear respiratory protection.
Regulation (EC) No. 1272 Hazard categories: Specific target orgar Hazard Statements: May cause damage 2.2. Label elements Regulation (EC) No. 1272 Hazard components fo Quartz Signal word: Pictograms: Hazard statements H373 Precautionary stateme P260 P285 P333+P313	Z/2008 In toxicity - repeated exposure: STOT RE 2 to organs (lung) through prolonged or repeated exposure if inhaled. Z/2008 r labelling Warning Vorticity May cause damage to organs (lung) through prolonged or repeated exposure if inhaled. Its Do not breathe dust. In case of inadequate ventilation wear respiratory protection. If skin irritation or rash occurs: Get medical advice/attention. Get medical advice/attention if you feel unwell.

PBT / vPvB substance.

SECTION 3: Composition/information on ingredients



according to Regulation (EC) No 1907/2006

Asplit[®] VEQ Powder

Revision date: 07.08.2018

Product code: 00359-1203

Page 2 of 8

3.2. Mixtures

Chemical characterization

Mixture of the following substances with non-hazardous admixtures

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
14808-60-7	Quartz			< 5 %	
	231-545-4				
	STOT RE 1; H372				
94-36-0	Dibenzoyl peroxide			< 1 %	
	202-327-6	617-008-00-0	01-2119511472-50		
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 10); H241 H319 H317 H400				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove and wash contaminated clothing before re-use.

After inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. In the event of symptoms refer for medical treatment.

After contact with skin

No specific precautions required.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

In the event of symptoms refer for medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure if inhaled. [lung] When dust is produced, slight irritations of eyes and mucous membranes are possible. Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough. May cause sensitization of susceptible persons by skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

No data available



according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.08.2018

Product code: 00359-1203

Page 3 of 8

5.3. Advice for firefighters

In case of fire, wear suitable respiratory equipment with positive air supply. Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of respirable dust, use a self-contained breathing apparatus. Ensure adequate ventilation. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Pick up mechanically, avoiding dust, and provide disposal in suitable recipients. Where possible recycling is preferred to disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Avoid the formation and deposition of dust. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

No materials to be especially mentioned.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

filler

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL



according to Regulation (EC) No 1907/2006

Asplit[®] VEQ Powder

Revision date: 07.08.2018

Product code: 00359-1203

Page 4 of 8

Additional advice on limit values

Obey TLV for common dust, if applicable.

8.2. Exposure controls

Appropriate engineering controls

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Protective and hygiene measures

Do not breathe dust. Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

Remove and wash contaminated clothing before re-use.

Eye/face protection

Safety goggles with side protection (EN 166).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing

Respiratory protection

Dust mask (EN 149)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Powder
Colour:	Grey
Odour:	Odourless
nH-Value	

pH-Value:	n.d.
Changes in the physical state	
Melting point:	n.d.
Initial boiling point and boiling range:	n.d.
Sublimation point:	n.d.
Softening point:	n.d.
Flash point:	n.a.
Flammability	
Solid:	n.d.
Gas:	n.a.
Explosive properties The product is not explosive.	
Lower explosion limits:	n.a.
Upper explosion limits:	n.a.
Ignition temperature:	n.a.
Auto-ignition temperature	

Test method



according to Regulation (EC) No 1907/2006

	Asplit® VEQ Powder	
Revision date: 07.08.2018	Product code: 00359-1203	Page 5 of 8
Solid:	n.d.	
Gas:	n.a.	
Decomposition temperature:	n.d.	
Oxidizing properties Not oxidising.		
Vapour pressure:	n.a.	
Density:	n.d.	
Bulk density:	1370 kg/m³	
Water solubility: (at 20 °C)	More or less insoluble	
Solubility in other solvents n.d.		
Partition coefficient:	n.d.	
Viscosity / dynamic:	n.a.	
Viscosity / kinematic:	n.a.	
Flow time:	n.a.	
Vapour density:	n.a.	
Evaporation rate:	n.a.	
Solvent separation test:	0 %	
Solvent content:	0 %	
9.2. Other information		

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

Not known.

10.5. Incompatible materials

No materials to be especially mentioned.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available.

Irritation and corrosivity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Asplit[®] VEQ Powder

Revision date: 07.08.2018

Product code: 00359-1203

Page 6 of 8

Sensitising effects

Contains Dibenzoyl peroxide. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs (lung) through prolonged or repeated exposure if inhaled. (Quartz)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

When dust is produced, slight irritations of eyes and mucous membranes are possible. Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough. May cause sensitization of susceptible persons by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

No data available

Further information

Ecological injuries are not known or expected under normal use. Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

080299

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations. Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken



according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.08.2018

Product code: 00359-1203

Page 7 of 8

for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID) 14.1. UN number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group: No dangerous good in sense of this transport regulation. Inland waterways transport (ADN) 14.1. UN number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group: No dangerous good in sense of this transport regulation. Marine transport (IMDG) No dangerous good in sense of this transport regulation. 14.1. UN number: 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.4. Packing group: Air transport (ICAO-TI/IATA-DGR) No dangerous good in sense of this transport regulation. 14.1. UN number: 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group: No dangerous good in sense of this transport regulation. 14.5. Environmental hazards ENVIRONMENTALLY HAZARDOUS: no 14.6. Special precautions for user No dangerous good in sense of this transport regulation. 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

0	
2004/42/EC (VOC):	0 %
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.



according to Regulation (EC) No 1907/2006

Asplit[®] VEQ Powder

Revision date: 07.08.2018

Product code: 00359-1203

Page 8 of 8

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
- IMDG = International Maritime Code for Dangerous Goods
- IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.
H400	Very toxic to aquatic life.
EUH208	Contains Dibenzoyl peroxide. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)