

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP CEMENT FD-BL

Art.-No.

511 1190, 511 1957, 511 2152, 511 2200, 511 3041, 511 3042, 511 3096, 511 3209, 514 1592, 515 9370, 515 9371, 515 9410, 515 9560, 515 9570, 515 9571, 517 3822, 599 2200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 100
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number: INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Acute 1

Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

n-Heptane

Acetone

Zinc bis(dibutyldithiocarbamate)

Signal word: Danger

Pictograms:





Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 2 of 11

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.
P501	Dispose of contents/container to in accordance with local and national regulations.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation in organic solvents

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 3 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
142-82-5	n-Heptane			< 85 %
	205-563-8	601-008-00-2	01-2119457603-38	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			
67-64-1	Acetone			< 25 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
136-23-2	Zinc bis(dibutyldithiocarbamate)			< 5 %
	205-232-8	006-081-00-9	01-2119535161-51	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H315 H319 H317 H335 H400 H410			
111-92-2	di-n-butylamine			< 1 %
	203-921-8	612-049-00-0	01-2119475606-30	
	Flam. Liq. 3, Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H226 H330 H311 H302 H314 H318			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

After inhalation

- Move to fresh air in case of accidental inhalation of vapours.
- Seek medical treatment immediately.

After contact with skin

- Wash off with soap and plenty of water.
- Consult a doctor if skin irritation persists.

After contact with eyes

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Seek medical treatment by eye specialist.

After ingestion

- Do not induce vomiting.
- Rinse out mouth and give plenty of water to drink.
- Never give anything by mouth to an unconscious person.
- Summon a doctor immediately.
- Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

- May cause drowsiness or dizziness.
- Causes serious eye irritation.
- Causes skin irritation.
- May cause an allergic skin reaction.
- Attention. Beware, danger of aspiration.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 4 of 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Do not smoke - volatile.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 5 of 11

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
142-82-5	n-Heptane	500	2085		TWA (8 h)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Treat subsequently with skin cream.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:
Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 6 of 11

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless, Milky
Odour:	Hydrocarbon-like

Test method

pH-Value:	n.d.
-----------	------

Changes in the physical state

Melting point:	n.d.
Initial boiling point and boiling range:	> 56 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 22 °C DIN EN ISO 3679

Flammability

Solid:	n.a.
Gas:	n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,1 vol. %
Upper explosion limits:	13,0 vol. %
Ignition temperature:	215 °C

Auto-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n.d.
----------------------------	------

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	247 hPa
--------------------------------	---------

Density (at 20 °C):	0,72 g/cm ³
Bulk density:	n.a.

Water solubility: (at 20 °C)	Partially miscible
---------------------------------	--------------------

Solubility in other solvents

n.d.

Partition coefficient:	n.d.
------------------------	------

Viscosity / dynamic:	5000 mPa·s
----------------------	------------

Viscosity / kinematic: (at 40 °C)	514 - 524 mm ² /s
--------------------------------------	------------------------------

Flow time:	> 30 s 3 DIN/ISO 2431
------------	-----------------------

Vapour density:	n.d.
-----------------	------

Evaporation rate:	n.d.
-------------------	------

Solvent separation test:	0 %
--------------------------	-----

Solvent content:	< 95 %
------------------	--------

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 7 of 11

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.
No toxicological data available.

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Zinc bis(dibutyldithiocarbamate))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (n-Heptane; Acetone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience**Other observations**

May cause irritation of the mucous membranes.
Effects of breathing high concentrations of vapour may include: Headache, dizziness, weakness, unconsciousness.
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
Attention. Beware, danger of aspiration!



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 8 of 11

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

n-Heptane

LC50/Carassius auratus/24 h = 4 mg/l

EC50/Daphnia magna/48 h = 1,5 mg/l

Acetone

LC50/Oncorhynchus mykiss/96 h > 1000 mg/l

EC50/Daphnia magna/48 h > 1000 mg/l

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 9 of 11

Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives (n-Heptane)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: No
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 10 of 11

IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC):	< 95 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	--

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT FD-BL

Revision date: 23.09.2019

Product code: 00156-0313

Page 11 of 11

LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)