

according to Regulation (EC) No 1907/2006

**TIP TOP COROFLAKE 23 LSE** 

Revision date: 17.07.2019

Product code: 00359-1021

Page 1 of 12

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP COROFLAKE 23 LSE

Art.-No.

590 0806, 590 0813

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Spray coating material

### 1.3. Details of the supplier of the safety data sheet

Company name:	TIP TOP Oberflaechenschutz Elbe GmbH	
Street:	Heuweg 4	
Place:	D-06886 Wittenberg	
Telephone:	+49(0)3491/635-50	Telefax:+49(0)3491/635-552
Responsible Department:	Responsible for the safety data sheet: sds@g	gbk-ingelheim.de
1.4. Emergency telephone	INTERNATIONAL: +49 - (0) 6132 - 84463, G	BK GmbH (24h - 7d/w - 365d/a)
<u>number:</u>	In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111	

### SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 3 Acute toxicity: Acute Tox. 4 Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Reproductive toxicity: Repr. 2 Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 1 Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Flammable liquid and vapour. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

Styrene Methacrylic acid

Signal word:

# Pictograms:





according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 2 of 12

Hazard statements					
H226	Flammable liquid and vapour.				
H332	Harmful if inhaled.				
H315	Causes skin irritation.				
H319	Causes serious eye irritation.				
H361d	Suspected of damaging the unborn child.				
H335	May cause respiratory irritation.				
H372	Causes damage to organs through prolonged or repeated exposure.				
H412	Harmful to aquatic life with long lasting effects.				
Precautionary statemen	Precautionary statements				
P202	Do not handle until all safety precautions have been read and understood.				
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.				
P260	Do not breathe vapour.				
P280	Wear protective gloves/protective clothing/eye protection/face protection.				
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.				
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.				
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.				
P405	Store locked up.				

#### Special labelling of certain mixtures

EUH208

Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

### **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### **Chemical characterization**

Epoxide-vinyl ester-resin in styrene



according to Regulation (EC) No 1907/2006

# **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 3 of 12

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification	•	•	
100-42-5	Styrene			< 30 %
	202-851-5	601-026-00-0	01-2119457861-32	
		Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, 332 H315 H319 H335 H372 H304 H4		
79-41-4	Methacrylic acid			< 3 %
	201-204-4	607-088-00-5	01-2119463884-26	
	Acute Tox. 4, Acute Tox. 4, Acute T	ox. 4, Skin Corr. 1A, STOT SE 3; H3	32 H312 H302 H314 H335	
75-57-0	Tetramethylammonium chloride			< 1 %
	200-880-8		01-2119970924-26	
	Acute Tox. 2, Acute Tox. 3, Skin Irr H411	it. 2, STOT SE 1, Aquatic Chronic 2;	H300 H311 H315 H370	
27253-31-2	Neodecanoic acid, cobalt salt			< 1 %
	248-373-0		01-2119970733-31	
	Acute Tox. 4, Skin Sens. 1, STOT	RE 1, Aquatic Chronic 3; H302 H317	H372 H412	
123-31-9	Hydroquinone			< 0,1 %
	204-617-8	604-005-00-4	01-2119524016-51	
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 10); H351 H341 H302 H318 H317 H400			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

### After inhalation

Move to fresh air in case of accidental inhalation of vapours. Seek medical treatment immediately.

#### After contact with skin

Wash off immediately with soap and plenty of water. Treat subsequently with skin cream. Consult a doctor if skin irritation persists.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult (eye) doctor immediately.

#### After ingestion

Do not induce vomiting. Summon a doctor immediately. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Induce vomiting only upon the advice of a physician.

## 4.2. Most important symptoms and effects, both acute and delayed

### Harmful if inhaled.



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 4 of 12

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure. (the ear)

Suspected of damaging the unborn child.

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce: carbon monoxide and carbon dioxide Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

### Additional information

Vapours are heavier than air and spread along ground. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet. Collect contaminated firefighting water separately, must not be discharged into the drains. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Remove persons to safety. Use personal protective clothing. Keep away sources of ignition.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

### Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Use only in thoroughly ventilated areas.



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 5 of 12

Provide suitable extraction at the processing machines.

### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to anti-explosion rules. Avoid temperatures above 50°C.

### Hints on joint storage

Incompatible with: Oxidizing agents, Metal halogenides, Peroxides

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Spray coating material

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
123-31-9	Hydroquinone	-	0.5		TWA (8 h)	WEL
79-41-4	Methacrylic acid	20	72		TWA (8 h)	WEL
		40	143		STEL (15 min)	WEL
12001-26-2	Mica, total inhalable	-	10		TWA (8 h)	WEL
100-42-5	Styrene	100	430		TWA (8 h)	WEL
		250	1080		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

### 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Pay attention to explosion protection guidelines.

### Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166). Eye wash bottle with pure water (EN 15154).

### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 6 of 12

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

### Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Solvent-resistant apron (EN 467).

### **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid		
Colour:	Yellowish		
Odour:	Pungent		
		I	Test method
pH-Value:		n.d.	
Changes in the physical state			
Melting point:		n.d.	
Initial boiling point and boiling range	je:	n.d.	
Sublimation point:		n.a.	
Softening point:		n.d.	
Flash point:		35 °C	
Flammability Solid:		n.a.	
Gas:		n.a.	
Explosive properties The product is considered non	-explosive; nevertheless expl	osive vapour/air mixture can be	generated.
Lower explosion limits:		1,1 vol. %	
Upper explosion limits:		n.d.	
Ignition temperature:		490 °C	
Auto-ignition temperature			
Solid:		n.a.	
Gas:		n.a.	
Decomposition temperature:		n.d.	
Oxidizing properties Not oxidising.			
Vapour pressure: (at 20 °C)		6 hPa	
Density:		1,13 ± 0,05 g/cm³	ISO 2811
Bulk density:		n.a.	
Water solubility: (at 20 °C)		Immiscible	
Solubility in other solvents n.d.			
Partition coefficient:		n.d.	
ision No: 1,2	GB -		Prii



#### according to Regulation (EC) No 1907/2006

	TIP TOP COROFLAKE 23 LSE	
Revision date: 17.07.2019	Product code: 00359-1021	Page 7 of 12
Viscosity / dynamic:	2750 ± 250 mPa⋅s	ISO 2555
Viscosity / kinematic: (at 40 °C)	> 20,5 mm²/s	
Flow time:	> 40 s	Ford beaker, no. 6
Vapour density:	n.d.	
Evaporation rate:	n.d.	
Solvent separation test:	< 3 %	
Solvent content:	< 5 %	
9.2. Other information		

No data available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No decomposition if stored and applied as directed.

## 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents. Reactions with peroxides.

#### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive at intensive warming. Heating can release vapours which can be ignited. Avoid temperatures above 50°C. If heating up polymerisation.

### 10.5. Incompatible materials

Metal halogenides, oxidizing agents, Peroxides

# 10.6. Hazardous decomposition products

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases). Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### Acute toxicity

Harmful if inhaled. No toxicological data available. Styrene LD50/oral/rat: 5000 mg/kg LD50/dermal/rat: > 2000 mg/kg LC50/inhalation/rat: 11,8 mg/l/4h

# Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

### Sensitising effects

Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.

### Carcinogenic/mutagenic/toxic effects for reproduction



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 8 of 12

Suspected of damaging the unborn child. (Styrene) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause respiratory irritation. (Styrene; Methacrylic acid)

### STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Styrene)

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### Practical experience

#### Other observations

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecological data are not available. Harmful to aquatic life with long lasting effects. Styrene LC50/Pimephales promelas/96 h = 4,02 mg/kg EC50/Daphnia magna/48 h = 4,7 mg/kg EC50/Pseudokirchneriela subcapitata/72 h > 4,9 mg/kg

#### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No data available

# 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Other adverse effects

Hazardous water pollutant.

Product is toxic to fish and their nutrient animals.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Can be incinerated, when in compliance with local regulations. Where possible recycling is preferred to disposal.

### Waste disposal number of waste from residues/unused products



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 9 of 12

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1866
14.2. UN proper shipping name:	Resin solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

#### Other applicable information (land transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 I (subsection 2.2.3.1.5 ADR).

UN 1866

ļ	In	land	waterways	transport (ADN)	
		14.	1. UN numb	er:	

14.2. UN proper shipping name:	Resin solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Other applicable information (inland v Viscous substance - excepted quar	waterways transport) ntity if in containers with a capacity up to 450 I (subsection 2.2.3.1.5 ADN).

#### Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1866
14.2. UN proper shipping name:	Resin solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



according to Regulation (EC) No 1907/2006

# **TIP TOP COROFLAKE 23 LSE**

	TIF TOF COROFLARE 23 LSE	
Revision date: 17.07.2019	Product code: 00359-1021	Page 10 of 12
	3	
Marine pollutant: Limited quantity:	No	
Excepted quantity:	5 L / 30 kg E1	
EmS:	F-E, S-E	
Other applicable information (marine tr Viscous substance - excepted quanti Code).	ransport) ty if in containers with a capacity up to 30 I (subsection 2.3.2.5 IMDG	i
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1866	
14.2. UN proper shipping name:	Resin solution	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
Hazard label:	3	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	355 60 L	
IATA-packing instructions - Cargo:	366	
IATA-max. quantity - Cargo:	220 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	
14.6. Special precautions for user Handle in accordance with good indu	strial hygiene and safety practice.	
14.7. Transport in bulk according to Annex	<u>k II of Marpol and the IBC Code</u>	
The transport takes place only in app	roved and appropriate packaging.	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental reg	ulations/legislation specific for the substance or mixture	
EU regulatory information		
2004/42/EC (VOC):	< 5 %; < 90 g/l	
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'work protection guideline' (94/33/EC). Observe employment restrunder the Maternity Protection Directive (92/85/EEC) for expecta	rictions

### Additional information

Consider Chemical prohibition regulation.

nursing mothers.



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 11 of 12

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm
- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

- vPvB = Very Persistent and very Bio-accumulative
- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration
- IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Neodecanoic acid, cobalt salt, May produce an allergic read

### EUH208 Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.

### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 23 LSE**

Revision date: 17.07.2019

Product code: 00359-1021

Page 12 of 12

level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations. (n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)