



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP COROFLAKE 29 C

Art.-No.

590 2100, 590 2110

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/mixture

Spray coating material

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635 50 Telephone: Telephone:

Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3
Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 1 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

Suspected of damaging the unborn child.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

# 2.2. Label elements

## Regulation (EC) No. 1272/2008

## Hazard components for labelling

Styrene

Methacrylic acid

methanol

N,N-Dimethylaniline

Signal word: Danger





according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 2 of 12

### Pictograms:









### **Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P273 Avoid release to the environment.

# Special labelling of certain mixtures

EUH208 Contains Neodecanoic acid, cobalt salt, 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-,

N-[(ethenylphenyl)methyl], Derivates, Hydrochlorides. May produce an allergic reaction.

# 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

## **Chemical characterization**

Epoxide-vinyl ester-resin in styrene



according to Regulation (EC) No 1907/2006

## **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 3 of 12

### **Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	Quartity
	GHS Classification			
100-42-5	Styrene	< 35 %		
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4 Aquatic Chronic 3; H226 H361d F			
79-41-4	Methacrylic acid			< 5 %
	201-204-4	607-088-00-5	01-2119463884-26	
	Acute Tox. 3, Acute Tox. 4, Acute	Tox. 4, Skin Corr. 1A, STC	T SE 3; H311 H332 H302 H314 H335	
67-56-1	methanol			< 1 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute			
27253-31-2	Neodecanoic acid, cobalt salt		< 1 %	
	248-373-0		01-2119970733-31	
	Acute Tox. 4, Skin Sens. 1, STOT			
75-57-0	Tetramethylammonium chloride			< 1 %
	200-880-8		01-2119970924-26	
	Acute Tox. 2, Acute Tox. 3, Skin II H411			
171869-89-9	1,2-Ethanediamine, N-[3-(trimethor Hydrochlorides	< 0,2 %		
	Eye Dam. 1, Skin Sens. 1; H318			
121-69-7	N,N-Dimethylaniline	< 0,2 %		
	204-493-5	612-016-00-0	01-2119935241-47	
	Carc. 2, Acute Tox. 3, Acute Tox.			
123-31-9	1,4-Dihydroxybenzene	< 0,1 %		
	204-617-8	604-005-00-4	01-2119524016-51	
	Carc. 2, Muta. 2, Acute Tox. 4, Ey H341 H302 H318 H317 H400			

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.

## After contact with skin

Wash off immediately with soap and plenty of water.

Treat subsequently with skin cream.

Consult a doctor if skin irritation persists.





according to Regulation (EC) No 1907/2006

## **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 4 of 12

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult (eye) doctor immediately.

### After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

## 4.2. Most important symptoms and effects, both acute and delayed

Harmful by inhalation.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure. (the ear)

Suspected of damaging the unborn child.

Attention. Beware, danger of aspiration.

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

### Unsuitable extinguishing media

Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

## Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

## 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.



TIP TOP Oberflaechenschutz Elbe GmbH

according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 5 of 12

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Provide suitable extraction at the processing machines.

### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Avoid temperatures above 50°C.

# Hints on joint storage

Incompatible with:

Oxidizing agents, Metal halogenides, Peroxides

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Spray coating material

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 6 of 12

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
123-31-9	Hydroquinone	-	0.5		TWA (8 h)	WEL
79-41-4	Methacrylic acid	20	72		TWA (8 h)	WEL
		40	143		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
121-69-7	N,N-Dimethylaniline	5	25		TWA (8 h)	WEL
		10	50		STEL (15 min)	WEL
100-42-5	Styrene	100	430		TWA (8 h)	WEL
		250	1080		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Pay attention to explosion protection guidelines.

### Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

# Eye/face protection

Eye wash bottle with pure water (EN 15154).

Tightly fitting goggles (EN 166).

## Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

## Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Solvent-resistant apron (EN 467).

# Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Viscous liquid
Colour: Black
Odour: Like styrene

Test method

pH-Value:



according to Regulation (EC) No 1907/2006


	according to Regulation (EC) No 1907/2006					
TIP TOP COROFLAKE 29 C						
Revision date: 30.07.2019	Product code: 00359-1031	Page 7 of 12				
Changes in the physical state						
Melting point:	n.d.					
Initial boiling point and boiling range:	n.d.					
Sublimation point:	n.d.					
Softening point:	n.d.					
Pour point:	n.d.					
Flash point:	35 °C					
Flammability						
Solid:	n.a.					
Gas:	n.a.					
Explosive properties  The product is considered non-exp	olosive; nevertheless explosive vapour/air mixture can be	generated.				
Lower explosion limits:	1,1 vol. %					
Upper explosion limits:	n.d.					
Ignition temperature:	490 °C					
Auto-ignition temperature						
Solid:	n.a.					
Gas:	n.a.					
Decomposition temperature:	n.d.					
Oxidizing properties  Not oxidising.						
Vapour pressure: (at 20 °C)	6 hPa					
Density:	1,16 - 1,24 g/cm³					
Bulk density:	n.a.					
Water solubility: (at 20 °C)	Immiscible					
Solubility in other solvents n.d.						
Partition coefficient:	n.d.					
Viscosity / dynamic: (at 25 °C)	2000 - 2500 mPa·s					
Viscosity / kinematic: (at 40 °C)	> 20,5 mm²/s					
Flow time:	> 60 s	Ford beaker, no. 6				
Vapour density:	n.d.					
Evaporation rate:	n.d.					
Solvent separation test:	< 3 %					
Solvent content:	< 5 %					
	• /*					

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

9.2. Other information
No data available

No decomposition if stored and applied as directed.





according to Regulation (EC) No 1907/2006

## **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 8 of 12

## 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

Reactions with peroxides.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Avoid temperatures above 50°C.

If heating up polymerisation.

## 10.5. Incompatible materials

Oxidizing agents, Metal halogenides, Peroxides

### 10.6. Hazardous decomposition products

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### **Acute toxicity**

Harmful if inhaled.

No toxicological data available.

Styrene

LD50/oral/rat: 5000 mg/kg LD50/dermal/rat: > 2000 mg/kg LC50/inhalation/rat: 11,8 mg/l/4h

## Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

### Sensitising effects

Contains Neodecanoic acid, cobalt salt, 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-, N-[(ethenylphenyl)methyl], Derivates, Hydrochlorides. May produce an allergic reaction.

### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (Styrene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause respiratory irritation. (Styrene; Methacrylic acid)

# STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Styrene)

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

# **Practical experience**

### Other observations

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the





according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 9 of 12

product.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

Stvrene

LC50/Pimephales promelas/96 h = 4,02 mg/kg

EC50/Daphnia magna/48 h = 4,7 mg/kg

EC50/Pseudokirchneriela subcapitata/72 h > 4,9 mg/kg

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Other adverse effects

Hazardous water pollutant.

Product is toxic to fish and their nutrient animals.

### Further information

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

## Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

### Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 10 of 12



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

### Other applicable information (land transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 I (subsection 2.2.3.1.5 ADR).

### Inland waterways transport (ADN)

14.1. UN number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

### Other applicable information (inland waterways transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 I (subsection 2.2.3.1.5 ADN).

# Marine transport (IMDG)

14.1. UN number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



### Other applicable information (marine transport)

Viscous substance - excepted quantity if in containers with a capacity up to 30 I (subsection 2.3.2.5 IMDG Code).

# Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3





according to Regulation (EC) No 1907/2006

## **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 11 of 12



Limited quantity Passenger: Y344 / 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### 14.6. Special precautions for user

The transport takes place only in approved and appropriate packaging.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 69: methanol

2004/42/EC (VOC): < 5 %; < 90 g/l

Information according to 2012/18/EU P5c F

(SEVESO III):

P5c FLAMMABLE LIQUIDS

### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

# 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



according to Regulation (EC) No 1907/2006

### **TIP TOP COROFLAKE 29 C**

Revision date: 30.07.2019 Product code: 00359-1031 Page 12 of 12

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

### Relevant H and EUH statements (number and full text)

0.0 tant	or cutomonto (number una run text)
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Neodecanoic acid, cobalt salt, 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-, N-[(ethenylphenyl)methyl], Derivates, Hydrochlorides. May produce an allergic reaction.

### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)