



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 2 of 12

**Pictograms:****Hazard statements**

H226	Flammable liquid and vapour.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take precautionary measures against static discharge.
P260	Do not breathe vapour.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local and national regulations.

**Special labelling of certain mixtures**

EUH204	Contains isocyanates. May produce an allergic reaction.
--------	---

**2.3. Other hazards**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

**3.2. Mixtures****Chemical characterization**

Aliphatic polyisocyanate



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 3 of 12

## Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
105431-79-6	Aliphatic polyisocyanate prepolymer			20 - 25 %
	Skin Sens. 1; H317			
7727-43-7	Barium sulphate			10 - 12,5 %
	231-784-4		01-2119491274-	
1330-20-7	Xylene (mixed isomers)			5 - 10 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
64742-95-6	Solvent naphtha (petroleum)			5 - 10 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
108-65-6	2-Methoxy-1-methylethyl acetate			5 - 10 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3; H226			
100-41-4	Ethyl benzene			1 - 2,5 %
	202-849-4		01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H332 H373 H304 H412			
82919-37-7	Methyl(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate			1 - 2,5 %
	280-060-4			
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
4083-64-1	4-isocyanatosulphonyltoluene			1 - 2,5 %
	223-810-8	615-012-00-7	01-2119980050-47	
	Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, STOT SE 3; H315 H319 H334 H335 EUH014			
	Isophorone diisocyanate, oligomer			0,5 - 1 %
	931-312-3		01-2119488734-24	
	Skin Sens. 1, STOT SE 3; H317 H335			
4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate			0,5 - 1 %
	223-861-6	615-008-00-5	01-2119490408-31	
	Acute Tox. 1, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, Aquatic Chronic 2; H330 H315 H319 H334 H317 H335 H411			
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate			0,5 - 1 %
	255-437-1			
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
162627-17-0	Polyaminoamide salt			< 0,5 %
	605-296-0		01-2119970640-38	
	Skin Sens. 1A; H317			

Full text of H and EUH statements: see section 16.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 4 of 12

#### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.  
If you feel unwell, seek medical advice.  
Take away from danger area and lay down affected person.  
In case of the person being unconscious put him/her in a stable side position.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
Refer for medical treatment.  
If patient is not breathing, apply artificial respiration.

#### After contact with skin

Wash off with soap and plenty of water.  
Consult a doctor if skin irritation persists.  
Do not use solvents or thinners.

#### After contact with eyes

Remove contact lens.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

#### After ingestion

Do not induce vomiting.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Toxic if inhaled.  
Causes skin irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (HCN)  
Isocyanates (NCO).



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 5 of 12

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective suit.

#### **Additional information**

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

Inform competent authority about release into the sewage, ground or into waters.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Container should not be gas-tight closed.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

Keep a good ventilation and air-exhaust at the place of work.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

When using do not eat, drink or smoke.

Do not empty container under pressure. No pressure tank!

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

##### **Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion protection rules.

Protect from heat and direct solar radiation.

Storage temperature between 15°C to 30°C

##### **Advice on storage compatibility**

Incompatible with:

Oxidizing agents

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROPUR COVER RAL**

Revision date: 18.09.2017

Product code: 00359-1234

Page 6 of 12

Acids and bases.  
Water, amines, alcohols

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

Coating component

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
7727-43-7	Barium sulphate, respirable dust	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Remove and wash contaminated clothing before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).  
Eye wash bottle with pure water (EN 15154).

**Hand protection**

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 7 of 12

recommendations given by the manufacturer of protective gloves.

#### Skin protection

Long sleeved clothing (EN 368).

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Various
Odour:	Characteristic

#### Test method

#### Changes in the physical state

Initial boiling point and boiling range:	139 °C	Xylene (mixed isomers)
Flash point:	28 °C	DIN 53213

#### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	2,47 vol. %	Ethyl benzene
Upper explosion limits:	8,1 vol. %	Ethyl benzene
Ignition temperature:	280 °C	

#### Oxidizing properties

Not fire-promoting.

Vapour pressure: (at 20 °C)	1,21 hPa
Density (at 20 °C):	1,32 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	Immiscible
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Flow time: (at 20 °C)	120 s 4 DIN 53211
Solvent content:	28 %

### 9.2. Other information

Solid content:	72 %
----------------	------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents  
Reacts with: Water, amines, alcohols

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 8 of 12

Heating can release vapours which can be ignited.  
Vapour/air-mixtures are explosive at intense warming.

#### **10.5. Incompatible materials**

Strong oxidizing agents  
Strong acids and strong bases  
Water, amines, alcohols

#### **10.6. Hazardous decomposition products**

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide gas, Isocyanates

## SECTION 11: Toxicological information

### **11.1. Information on toxicological effects**

#### **Acute toxicity**

Toxic if inhaled.  
No toxicological data available.

#### **Irritation and corrosivity**

Causes skin irritation.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### **Sensitising effects**

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (4-isocyanatosulphonyltoluene; 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate)  
May cause an allergic skin reaction. (Aliphatic polyisocyanate prepolymer; Methyl(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; Isophorone diisocyanate, oligomer; 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; Polyaminoamide salt)

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### **Other observations**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.  
A longer or repeated contact may lead to irritation of eyes and mucous membranes.  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.  
With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

## SECTION 12: Ecological information

### **12.1. Toxicity**

Ecological data are not available.  
Toxic to aquatic life with long lasting effects.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 9 of 12

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

Hazardous water pollutant.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Advice on disposal**

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

##### **Waste disposal number of waste from residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

##### 14.1. UN number:

UN 1992

##### 14.2. UN proper shipping name:

FLAMMABLE LIQUID, TOXIC, N.O.S. (Xylene (mixed isomers), Isophorone diisocyanate)

##### 14.3. Transport hazard class(es):

3

##### 14.4. Packing group:

III

Hazard label:

3+6.1



Classification code:

FT1

Limited quantity:

5 L / 30 kg

Excepted quantity:

E1

Transport category:

3

Hazard No:

36

Tunnel restriction code:

D/E

#### **Inland waterways transport (ADN)**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 10 of 12

**14.1. UN number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (Xylene (mixed isomers), Isophorone diisocyanate)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3+6.1



Classification code: FT1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1

**Other applicable information (inland waterways transport)**

Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

**Marine transport (IMDG)**

**14.1. UN number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (Xylene (mixture of isomers), Isophorone diisocyanate, Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3+6.1



Marine pollutant: Yes  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1992  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S. (Xylene (mixture of isomers), Isophorone diisocyanate)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3+6.1



Limited quantity Passenger: 2 L  
Passenger LQ: Y343  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROPUR COVER RAL

Revision date: 18.09.2017

Product code: 00359-1234

Page 11 of 12

ENVIRONMENTALLY HAZARDOUS: yes



#### **14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

#### **14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: Solvent naphtha (petroleum)

2004/42/EC (VOC): 367 g/l

##### **National regulatory information**

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D):

2 - water contaminating

#### **15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### **Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### **Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROPUR COVER RAL**

Revision date: 18.09.2017

Product code: 00359-1234

Page 12 of 12

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*