



according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Art.-No.

580 0690, 580 0724, 580 1527

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating component

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-552

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3 Acute toxicity: Acute Tox. 2 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Resp. Sens. 1 Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.

Fatal if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Xylene (mixed isomers)

Isophorone diisocyanat, homopolymer

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Aliphatic polyisocyanate

4-isocyanatosulphonyltoluene

Methyl(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate





according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 2 of 12

Signal word: Danger

Pictograms:







Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

H330 Fatal if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P273 Avoid release to the environment.

P501 Dispose of contents/container to in accordance with local and national regulations.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aliphatic polyisocyanate



according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 3 of 12

Hazardous components

CAS No	Chemical name	Quantity			
	EC No	Index No	REACH No		
	GHS Classification	•	•		
1330-20-7	Xylene (mixed isomers)	Xylene (mixed isomers)			
	215-535-7	601-022-00-9	01-2119488216-32		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 1, Aquatic Chronic 3; H226 F				
53880-05-0	Isophorone diisocyanat, homopol	ymer		5 - 10 %	
	500-125-5				
	Skin Sens. 1, STOT SE 3; H317 H	H335	•		
4098-71-9	3-isocyanatomethyl-3,5,5-trimethy	/lcyclohexyl isocyanate		5 - 10 %	
	223-861-6	615-008-00-5	01-2119490408-31		
	Acute Tox. 1, Skin Irrit. 2, Eye Irrit 2; H330 H315 H319 H334 H317 I	ns. 1, STOT SE 3, Aquatic Chronic			
100-41-4	Ethyl benzene			2,5 - 5 %	
	202-849-4		01-2119489370-35		
	Flam. Liq. 2, Acute Tox. 4, STOT H412				
160994-68-3	Aliphatic polyisocyanate	1		< 5 %	
	A + T + OI : O + OTOT	10504 (100 100)			
	Acute Tox. 4, Skin Sens. 1, STOT	SE 3, Aquatic Chronic 3; F	332 H317 H335 H412		
108-65-6	2-Methoxy-1-methylethyl acetate			< 5 %	
	203-603-9	607-195-00-7	01-2119475791-29		
1000 01 1	Flam. Liq. 3, STOT SE 3; H226 H	4 0 5 0			
4083-64-1	4-isocyanatosulphonyltoluene	1		1 - 2,5 %	
	223-810-8	615-012-00-7	01-2119980050-47		
	Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, STOT SE 3; H315 H319 H334 H335 EUH014				
82919-37-7	Methyl(1,2,2,6,6-pentamethyl-4-p	iperidyl)sebacate		< 0,5 %	
	280-060-4				
	Skin Sens. 1, Aquatic Acute 1, Ac) H410		
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piper	idyl)sebacate		< 0,5 %	
	255-437-1				
	Skin Sens. 1, Aquatic Acute 1, Ac				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

Take away from danger area and lay down affected person.

In case of the person being unconscious put him/her in a stable side position.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

Refer for medical treatment.



according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 4 of 12

If patient is not breathing, apply artificial respiration.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

Do not use solvents or thinners.

After contact with eyes

Remove contact lens.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Fatal if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause respiratory irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause damage to organs through prolonged or repeated exposure.

Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

Isocyanates (NCO).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.



TIP TOP Oberflaechenschutz Elbe GmbH

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 5 of 12

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Inform competent authority about release into the sewage, ground or into waters.

Inform competent authority about release into the sewage, ground or into waters.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Container should not be gas-tight closed.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Keep a good ventilation and air-exhaust at the place of work.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

When using do not eat, drink or smoke.

Do not empty container under pressure. No pressure tank!

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion protection rules.

Protect from heat and direct solar radiation.

Storage temperature between 15°C to 30°C

Hints on joint storage

Incompatible with:

Oxidizing agents

Acids and bases.

Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Coating component

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



TIP TOP Oberflaechenschutz Elbe GmbH

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 6 of 12

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	I	Post shift

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothing before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Various
Odour: Characteristic



according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 7 of 12

		Test method
pH-Value:	n.a.	
Changes in the physical state		
Melting point:	n.d.	
Initial boiling point and boiling range:	139 °C	*)
Sublimation point:	n.a.	
Softening point:	n.d.	
Flash point:	35 °C	DIN 53213
Flammability		
Solid:	n.a.	
Gas:	n.a.	
Explosive properties		
The product is considered non explosive; nevertheless explosive vaneur/	air miytura can ba	gonorated

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

3,15 vol. % Lower explosion limits: Upper explosion limits: 8,1 vol. % Ignition temperature: 180 °C

Auto-ignition temperature

Solid: n.a. Gas: n.a. Decomposition temperature: n.d.

Oxidizing properties

Not oxidising.

Vapour pressure: 1,06 hPa

(at 20 °C)

Density (at 20 °C): 1,35 g/cm³ Bulk density: n.a. Water solubility: Immiscible

(at 20 °C)

Solubility in other solvents

n.d.

Partition coefficient: n.d. Viscosity / dynamic: n.d.

(at 20 °C)

Viscosity / kinematic: n.d.

Flow time: 200 s 4 DIN EN ISO 2431

(at 20 °C)

Vapour density:

Evaporation rate: n.d. ASTM D 3539

Solvent separation test: < 3 % Solvent content: < 25 %

9.2. Other information

Solid content: < 80 %

*) Xylene (mixed isomers)





according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 8 of 12

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Heating can release vapours which can be ignited.

Vapour/air-mixtures are explosive at intense warming.

10.5. Incompatible materials

Strong oxidizing agents

Strong acids and strong bases

Water, amines, alcohols

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

Hydrogen cyanide gas, Isocyanates

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Fatal if inhaled.

No toxicological data available.

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; 4-isocyanatosulphonyltoluene)

May cause an allergic skin reaction. (Isophorone diisocyanat, homopolymer;

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate; Aliphatic polyisocyanate;

Methyl(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Xylene (mixed isomers))

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.



TIP TOP Oberflaechenschutz Elbe GmbH

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 9 of 12

Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.

A longer or repeated contact my lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2929

14.2. UN proper shipping name: TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S.

(3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, Xylene (mixed

isomers))

14.3. Transport hazard class(es): 6.1
14.4. Packing group: II



according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 10 of 12

Hazard label: 6.1+3

Classification code: TF1

Limited quantity: 100 mL / 30 kg

Excepted quantity: E4 Transport category: Hazard No: 63 Tunnel restriction code: D/E

Inland waterways transport (ADN)

UN 2929 14.1. UN number:

TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S. 14.2. UN proper shipping name:

(3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, Xylene (mixed

isomers))

6.1 14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 6.1+3



Classification code: TF1

Limited quantity: 100 mL / 30 kg

Excepted quantity:

Marine transport (IMDG)

14.1. UN number: UN 2929

TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S. 14.2. UN proper shipping name:

(3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, Xylene (mixed

isomers))

6.1 14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label:

6.1+3



Marine pollutant: Nο

100 mL / 30 kg Limited quantity:

Excepted quantity: F4 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2929

14.2. UN proper shipping name: TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S.

(3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, Xylene (mixed

isomers))

14.3. Transport hazard class(es): 6.1 14.4. Packing group: Ш Hazard label: 6.1+3



TIP TOP Oberflaechenschutz Elbe GmbH

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 11 of 12



Limited quantity Passenger: 1 L
Passenger LQ: Y641
Excepted quantity: E4

IATA-packing instructions - Passenger: 654
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 662
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 286 g/l

Information according to 2012/18/EU H2 ACUTE TOXIC

(SEVESO III):

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



TIP TOP Oberflaechenschutz Elbe GmbH

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR NON ABRASIVE LS WITH ACTIVATOR A-1949 (MV 10:1)

Revision date: 17.03.2020 Product code: 00359-1247 Page 12 of 12

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)