# REMA INDP

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



#### **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**ESKANOL EF HARDENER 49 S** 

Art.-No.

10021, 10022

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Hardener

## 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4 Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Harmful if swallowed. Harmful if inhaled.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

# Regulation (EC) No. 1272/2008

#### Hazard components for labelling

Benzyl alcohol

3-Aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products

with m-phenylenebis(methylamine)

Xylylenediamine

Signal word: Danger



according to Regulation (EC) No 1907/2006



## **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 2 of 10

#### Pictograms:





#### **Hazard statements**

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P273 Avoid release to the environment.

## Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### **Chemical characterization**

Hardener based on aliphatic polyamines

Revision No: 1,0 GB - EN Print date: 30.03.2017



according to Regulation (EC) No 1907/2006



## **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 3 of 10

#### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
100-51-6	Benzyl alcohol			< 40 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4; H302			
2855-13-2	3-Aminomethyl-3,5,5-trimethylcyclohexylamine			< 30 %
	220-666-8	612-067-00-9	01-2119514687-32	
	Acute Tox. 4, Acute Tox. 4, Skin C H317 H412			
113930-69-1	4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)			< 20 %
	500-302-7		01-2119965162-39	
	Skin Corr. 1B, Eye Dam. 1, Skin			
1477-55-0	Xylylenediamine			< 15 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H332 H314 H317 H412 EUH071			
69-72-7	Salicylic acid			< 5 %
	200-712-3		01-2119486984-17	
	Acute Tox. 4, Eye Dam. 1; H302 H318			

Full text of H and EUH statements: see section 16.

## **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

## **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

## After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

# After ingestion

Do not induce vomiting.

Rinse mouth.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

## 4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

# REMA INTO

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



## **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 4 of 10

May cause an allergic skin reaction.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Fire-extinguishing activities according to surrounding.

#### Unsuitable extinguishing media

Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

## 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

#### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

## Advice on protection against fire and explosion

No special protective measures against fire required.

## 7.2. Conditions for safe storage, including any incompatibilities

Revision No: 1,0 GB - EN Print date: 30.03.2017

# REMA INTO

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



#### **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 5 of 10

# Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Protect against direct sun radiation.

Recommended storage temperature: 5°C - 35°C

#### Advice on storage compatibility

Incompatible with:

Oxidizing agents, Acids and bases.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

Hardener

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Additional advice on limit values

No data available.

#### 8.2. Exposure controls

# Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

#### **Hand protection**

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove < Vitoject 890> made by www.kcl.de. Splash protection: Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) > 10 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

# Skin protection

Long sleeved clothing (EN 368).

## **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

#### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Dark yellow
Odour: Amine like

Revision No: 1.0 GB - EN Print date: 30.03.2017

# REMA TOD

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



## **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 6 of 10

Test method

pH-Value (at 20 °C):

Changes in the physical state

Flash point: 94 °C (Calculated)

Lower explosion limits: n.d.

Upper explosion limits:

Ignition temperature: n.d. Vapour pressure: n.d.

Density (at 23 °C): approx. 1,001 g/cm³ ISO 2811-2

Water solubility: Immiscible

(at 20 °C)

Viscosity / dynamic: 70 - 110 mPa·s ISO 2884-1

(at 25 °C)

Flow time: 30 - 40 s 4 DIN 53211

(at 23 °C)

#### 9.2. Other information

No data available.

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

No decomposition if stored and applied as directed.

#### 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

## 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Protect against direct sun radiation.

## 10.5. Incompatible materials

Oxidizing agents, Acids and bases.

# 10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

# Acute toxicity

Harmful if swallowed or if inhaled.

No toxicological data available.

ATEmix/oral: > 2000 mg/kg

ATEmix/dermal: > 2000 mg/kg

ATEmix/inhalation: 4,688 mg/l/4h [Aerosol]

## Irritation and corrosivity

Causes severe skin burns and eye damage.

# REMA INITO

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



## **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 7 of 10

#### Sensitising effects

May cause an allergic skin reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

# 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

Hazardous water pollutant.

## **Further information**

Do not flush into surface water or sanitary sewer system.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Advice on disposal

Can be incinerated, when in compliance with local regulations.

#### Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

## Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

# REMA TOP

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006



## **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 8 of 10

## **SECTION 14: Transport information**

Land transport (ADR/RID)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethyl cyclohexylamine)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C7

Limited quantity: 1 L / 30 kg

Excepted quantity: E2
Transport category: 2
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

**14.1. UN number:** UN 2735

**14.2. UN proper shipping name:** POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C7
Limited quantity: 1 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

<u>14.1. UN number:</u> UN 2735

**14.2. UN proper shipping name:** POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine)

 14.3. Transport hazard class(es):
 8

 14.4. Packing group:
 II

 Hazard label:
 8



Marine pollutant:

Limited quantity:

Excepted quantity:

EmS:

No

1 L / 30 kg

E2

EmS:

F-A, S-B

Air transport (ICAO-TI/IATA-DGR)



according to Regulation (EC) No 1907/2006



#### **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 9 of 10

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(3-Aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 2 - water contaminating

## 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



according to Regulation (EC) No 1907/2006



#### **ESKANOL EF HARDENER 49 S**

Revision date: 30.03.2017 Product code: 00359-1321 Page 10 of 10

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H312	Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)