

REMATIP TOP AG

according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP FIXPASTE REMA GOO PART A

Art.-No.

525 3100, 525 3105, 594 2510

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Conveyor belt repair material

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Resp. Sens. 1 Respiratory or skin sensitisation: Skin Sens. 1

Carcinogenicity: Carc. 2

Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements: Fatal if inhaled. Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Dicyclohexylmethane-4,4'-di-isocyanate methylenediphenyl diisocyanate triethoxy(3-isocyanatopropyl)silane

Signal word: Danger





according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 2 of 11

Pictograms:

H315





Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Do not handle until all safety precautions have been read and understood. P202

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water. P302+P352

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if P305+P351+P338

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with isocyanates





according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 3 of 11

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification			
5124-30-1	Dicyclohexylmethane-4,4'-di-isocyanate			
	225-863-2	615-009-00-0	01-2119457437-31	
	Acute Tox. 2, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3; H330 H315 H319 H334 H317 H335			
26447-40-5	methylenediphenyl diisocyanate			1 - 15 %
	247-714-0	615-005-00-9		
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
24801-88-5	triethoxy(3-isocyanatopropyl)silane			1 - 5 %
	246-467-6			
	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, STOT SE 3; H330 H312 H302 H315 H319 H334 H335			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

If patient is not breathing, apply artificial respiration.

Refer for medical treatment.

After contact with skin

Wash contaminated skin with plenty of water and soap or with liquid polyethylene glycol.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the evelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse out mouth thoroughly with water.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Fatal if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause respiratory irritation.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed



REMATIP TOP AG

according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 4 of 11

Treat symptoms.

Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container should not be gas-tight closed.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

Do not breathe vapours.

Local exhaust.

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.



REMATIP TOP AG

according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 5 of 11

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Store only in original container at temperature of 30°C maximum (=86°F).

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Hints on joint storage

Exothermic reaction with:

Acids and bases.

Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

7.3. Specific end use(s)

Conveyor belt repair material

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

No data available

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www kcl de

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Single-use coverall

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).





according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 6 of 11

SECTION 9: Physical and chemical properties

Physical state: Liquid - viscous

Colour: Black Odour: Soft

Test method

pH-Value: n.d.

Changes in the physical state

Melting point: n.d. Initial boiling point and boiling range: $> 200 \,^{\circ}\text{C}$ Sublimation point: n.a. Softening point: n.d.

Pourpoint:

Flash point: > 140 °C Closed cup

Flammability

Solid: n.a. Gas: n.a.

Explosive properties

The product is not explosive.

Lower explosion limits:

Upper explosion limits:

n.d.

Ignition temperature:

n.d.

Auto-ignition temperature

Solid: n.a. Gas: n.a. Decomposition temperature: n.d.

Oxidizing properties

Not oxidising.

Vapour pressure: 5,33288 10-7 hPa

(at 20 °C)

Density (at 20 °C): 1,08 g/cm³
Bulk density: n.a.

Water solubility: Reacts with water.

(at 20 °C)

Solubility in other solvents

n.d.

Partition coefficient: n.d. 2500 - 4000 mPa·s Viscosity / dynamic: Viscosity / kinematic: n.d. Flow time: n.d. Vapour density: n.d. Evaporation rate: n.d. 0 % Solvent separation test: Solvent content: 0 %



REMATIP TOP AG

according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 7 of 11

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies. Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.5. Incompatible materials

Acids and bases.

Water, amines, alcohols

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Hydrogen cyanide gas, Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Fatal if inhaled.

No toxicological data available. ATEmix/oral: > 5000 mg/kg ATEmix/dermal: > 2000 mg/kg ATEmix/inhalation: < 0,5 mg/l

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Dicyclohexylmethane-4,4'-di-isocyanate; methylenediphenyl diisocyanate; triethoxy(3-isocyanatopropyl)silane)

May cause an allergic skin reaction. (Dicyclohexylmethane-4,4'-di-isocyanate; methylenediphenyl diisocyanate)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (methylenediphenyl diisocyanate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Dicyclohexylmethane-4,4'-di-isocyanate; methylenediphenyl diisocyanate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.





according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 8 of 11

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocvanates; therefore keep room aerated and ventilated.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Dicyclohexylmethane-4,4'-di-isocyanate

LC50/Danio rerio/96 h > 8,1 mg/l

EC50/Daphnia magna/48 h > 8,3 mg/l

ErC50 Desmodesmus subspicatus/72 h > 5 mg/l

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

In aqueous systems, formation of unsoluble and chemically inert (inactive) polyureas.

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information





according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 9 of 11

Land transport (ADR/RID)

14.1. UN number: UN 2206

14.2. UN proper shipping name: ISOCYANATE SOLUTION, TOXIC, N.O.S.

(Dicyclohexylmethane-4,4'-di-isocyanate, methylenediphenyl diisocyanate,

triethoxy(3-isocyanatopropyl)silane)

14.3. Transport hazard class(es): 6.

14.4. Packing group:IIIHazard label:6.1



Classification code: T1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1
Transport category: 2
Hazard No: 60
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 2206

14.2. UN proper shipping name: ISOCYANATE SOLUTION, TOXIC, N.O.S.

6.1

(Dicyclohexylmethane-4,4'-di-isocyanate, methylenediphenyl diisocyanate,

triethoxy(3-isocyanatopropyl)silane)

14.3. Transport hazard class(es):

14.4. Packing group:IIIHazard label:6.1



Classification code: T1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 2206

14.2. UN proper shipping name: ISOCYANATE SOLUTION, TOXIC, N.O.S.

(Dicyclohexylmethane-4,4'-di-isocyanate, methylenediphenyl diisocyanate,

triethoxy(3-isocyanatopropyl)silane)

14.3. Transport hazard class(es): 6.1 14.4. Packing group:

Hazard label: 6.1



Marine pollutant: No

Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-A, S-A

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2206





according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 10 of 11

14.2. UN proper shipping name: ISOCYANATE SOLUTION, TOXIC, N.O.S.

(Dicyclohexylmethane-4,4'-di-isocyanate, methylenediphenyl diisocyanate,

triethoxy(3-isocyanatopropyl)silane)

14.3. Transport hazard class(es):6.114.4. Packing group:IIIHazard label:6.1



Limited quantity Passenger: 2 L
Passenger LQ: Y642
Excepted quantity: E1

IATA-packing instructions - Passenger: 655
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 663
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Take the usual precautions when handling with chemicals.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 56: methylenediphenyl diisocyanate 2004/42/EC (VOC): 0 %

Information according to 2012/18/EU H2 ACUTE TOXIC

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Additional information

Consider Chemical prohibition regulation.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information



REMATIP TOP AG

according to Regulation (EC) No 1907/2006

TIP TOP FIXPASTE REMA GOO PART A

Revision date: 14.05.2020 Product code: 00156-0379 Page 11 of 11

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intér IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

• • • • • • • • • • • • • • • • • • • •	
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)