

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP PRIMER S 500-2

Art.-No.

525 2310, 525 2341, 525 2358, 525 2480, 525 2488

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Primer Coat

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Acute toxicity: Acute Tox. 4

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Flammable liquid and vapour.

Harmful in contact with skin.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Regulation (EC) No. 1272/2008**Hazard components for labelling**

Reaction mass of ethylbenzene and xylene

Signal word: Warning**Pictograms:****Hazard statements**

H226

Flammable liquid and vapour.

H312+H332

Harmful in contact with skin or if inhaled.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 2 of 10

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P314	Get medical advice/attention if you feel unwell.
P403+P235	Store in a well-ventilated place. Keep cool.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with aromatic hydrocarbons

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
	Reaction mass of ethylbenzene and xylene			60 - 80 %
			01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
108-88-3	toluene			< 1 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Treat subsequently with skin cream.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 3 of 10

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse mouth.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful in contact with skin or if inhaled.

Causes serious eye irritation.

May cause respiratory irritation.

Causes skin irritation.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide, carbon dioxide, sulphur oxides and nitrogen oxides (NO_x).

Hydrogen chloride gas.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 4 of 10

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- Keep container tightly closed.
- Use only in area provided with appropriate exhaust ventilation.
- In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

Advice on protection against fire and explosion

- Keep product and empty container away from heat and sources of ignition.
- Pay attention to anti-explosion rules.
- Do not smoke.
- Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep containers tightly closed in a cool, well-ventilated place.
- Keep away from heat and sources of ignition.

Hints on joint storage

- Incompatible with:
strong oxidizing agents, strong acids and strong bases

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Primer Coat

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

- Ensure adequate ventilation, especially in confined areas.
- Pay attention to explosion protection guidelines.

Protective and hygiene measures

- Do not inhale vapours.
- Avoid contact with eyes and skin.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Remove and wash contaminated clothes before re-use.

Eye/face protection

- Tightly fitting goggles (EN 166).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 5 of 10

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black
Odour:	Aromatic

Test method

pH-Value:	n.d.
-----------	------

Changes in the physical state

Melting point:	n.d.
Initial boiling point and boiling range:	n.d.
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	25 °C

Flammability

Solid:	n.a.
Gas:	n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	n.d.
Upper explosion limits:	n.d.
Ignition temperature:	460 °C (*)

Auto-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n.d.
----------------------------	------

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	n.d.
--------------------------------	------

Density (at 20 °C):	0,92 - 0,96 g/cm ³
---------------------	-------------------------------

Bulk density:	n.a.
---------------	------

Water solubility:	Immiscible
-------------------	------------

Partition coefficient:	n.d.
------------------------	------

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 6 of 10

Viscosity / dynamic:	200 - 2000 mPa·s
Viscosity / kinematic: (at 40 °C)	> 20,5 mm ² /s
Flow time: (at 20 °C)	70 - 120 s 4 DIN EN ISO 2431
Vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	0 %
Solvent content:	< 75 %

9.2. Other information

(*) Xylene (mixed isomers)

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapours may form explosive mixture with air.

10.5. Incompatible materials

Strong oxidizing agents.

Strong acids and strong bases

10.6. Hazardous decomposition productsCarbon monoxide, carbon dioxide, sulphur oxides and nitrogen oxides (NO_x).

Hydrogen chloride gas

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Harmful in contact with skin or if inhaled.

No toxicological data available.

ATEmix/dermal: ~ 1600 mg/kg

ATEmix/inhalation: ~ 15 mg/l (vapour)

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Reaction mass of ethylbenzene and xylene)

STOT-repeated exposure



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 7 of 10

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of ethylbenzene and xylene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Further information

Contact with eyes may cause irritation.

Inhalation of vapours in high concentration can cause narcotic effects.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 8 of 10

Land transport (ADR/RID)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: No
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 9 of 10



Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 48: toluene

2004/42/EC (VOC):	< 75%
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	--

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP PRIMER S 500-2

Revision date: 15.03.2019

Product code: 00156-0132

Page 10 of 10

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)