

according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP REMACOAT A-80 HP POLY colorless

Art.-No.

590 3355, 590 3385

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Resin component for 2K coating system

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50 Telefax:+49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Glyceryl poly(oxypropylene) triamine

Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)-

Diethylmethylbenzenediamine

6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine

Signal word: Danger

Pictograms:









Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 2 of 10

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P405 Store locked up.

P273 Avoid release to the environment.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of organic amines

Hazardous components

Chemical name			Quantity
EC No	Index No	REACH No	
GHS Classification	•	•	
22-8 Glyceryl poly(oxypropylene) triamine			< 35 %
Skin Irrit. 2, Eye Dam. 1,	Aquatic Chronic 3; H315 H318 H41	2	
0-0 Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)-			< 25 %
Acute Tox. 4, Skin Corr.	1B, Eye Dam. 1, Aquatic Chronic 3;	H302 H314 H318 H412	
Diethylmethylbenzenediamine			< 15 %
270-877-4	612-130-00-0	01-2119486805-25	
· ·		Acute 1, Aquatic Chronic 1; H312	
6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine			< 5 %
403-240-8	612-113-00-8	01-2119943036-42	
Acute Tox. 4, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H317 H400 H410			
	EC No GHS Classification Glyceryl poly(oxypropyle Skin Irrit. 2, Eye Dam. 1, Poly(oxy(methyl-1,2-etha Acute Tox. 4, Skin Corr. Diethylmethylbenzenedia 270-877-4 Acute Tox. 4, Acute Tox. H302 H319 H373 H400 H 6-Methyl-2,4-bis(methyltt) 403-240-8	EC No GHS Classification Glyceryl poly(oxypropylene) triamine Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H315 H318 H41 Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl) Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; Diethylmethylbenzenediamine 270-877-4 612-130-00-0 Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic / H302 H319 H373 H400 H410 6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine 403-240-8 612-113-00-8	EC No Index No REACH No GHS Classification Glyceryl poly(oxypropylene) triamine Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H315 H318 H412 Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)- Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H302 H314 H318 H412 Diethylmethylbenzenediamine 270-877-4 612-130-00-0 01-2119486805-25 Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H312 H302 H319 H373 H400 H410 6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine 403-240-8 01-2119943036-42

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

Consult a physician.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.





according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 3 of 10

In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.

Consult a physician.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).





according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 4 of 10

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Use only in well-ventilated areas.

Do not breathe vapours or spray mist.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Resin component for 2K coating system

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

No data available.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Do not breath vapours or spray mist.

Eye/face protection

Eye wash bottle with pure water (EN 15154).

Tightly fitting goggles (EN 166).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing (DIN EN ISO 6530)



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 5 of 10

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and che		
Physical state:	Viscous liquid	
Colour:	transparent	
Odour:	Amine like	
pH-Value:	n	Test method .d.
·	.,	.u.
Changes in the physical state		
Melting point:		.d.
Initial boiling point and boiling range:		.d.
Sublimation point:		.a.
Softening point:		.d.
Flash point:	> 100	°C
Flammability		
Solid:	n	a.
Gas:	n	a.
Explosive properties The product is not explosive.		
Lower explosion limits:	n	.d.
Upper explosion limits:	n	.d.
Ignition temperature:	n	.d.
Auto-ignition temperature Solid:	n	.a.
Gas:		.a.
Decomposition temperature:	n	.d.
Oxidizing properties Not oxidising.		
Vapour pressure:	n	.d.
Density (at 25 °C):	1,02 - 1,06 g/c	m³
Bulk density:		a.
Water solubility:	Immiscib	ole
Solubility in other solvents n.d.		
Partition coefficient:	n	.d.
Viscosity / dynamic: (at 25 °C)	1200 - 1800 mPa	ı·s
Viscosity / kinematic:	n	.d.
Flow time:	n	d.
Vapour density:	n	d.
Evaporation rate:	n	.d.
Solvent separation test:	0	%





according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 6 of 10

Solvent content: 0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

No toxicological data available. ATEmix/oral: approx. 1200 mg/kg ATEmix/dermal: > 2000 mg/kg ATEmix/inhalation: > 20 mg/l

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diethylmethylbenzenediamine)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Inhalation of vapours in high concentration may cause irritation of respiratory system.

After single absorption, risk of blood damage (methaemoglobinaemia).



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 7 of 10

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Severe hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C7
Limited quantity: 1 L / 30 kg



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 8 of 10

Excepted quantity: E2
Transport category: 2
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C7

Limited quantity: 1 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Marine pollutant: Yes
Limited quantity: 1 L / 30 kg
Excepted quantity: E2
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L

14.5. Environmental hazards



TIP TOP Oberflaechenschutz Elbe GmbH

according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless

Revision date: 12.06.2019 Product code: 00359-1339 Page 9 of 10

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 0 %

Information according to 2012/18/EU

(SEVESO III):

E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

Changes in chapter: 1

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 HP POLY colorless				
Revision date: 12.06.2019	Product code: 00359-1339	Page 10 of 10		
H312	Harmful in contact with skin.			
H314	Causes severe skin burns and eye damage.			
H315	Causes skin irritation.			
H317	May cause an allergic skin reaction.			
H318	Causes serious eye damage.			
H319	Causes serious eye irritation.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
H411	Toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)