

according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B

Revision date: 22.06.2017

Product code: 00359-1009

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP REMAFIX L COMP. B

Art.-No.

528 7055, 528 7070

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hard rubber surfacer

1.3. Details of the supplier of the safety data sheet

| Company name: | TIP TOP Oberflaechenschutz Elbe GmbH | | |
|-------------------------------------|--|-----------------------------|--|
| Street: | Heuweg 4 | | |
| Place: | D-06886 Wittenberg | | |
| Telephone: | +49(0)3491/635-50 | Telefax: +49(0)3491/635-552 | |
| Responsible Department: | Responsible for the safety data sheet: sds@gbk-ingelheim.de | | |
| 1.4. Emergency telephone number: | INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24 24 | | |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Skin corrosion/irritation: Skin Corr. 1B Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1A Reproductive toxicity: Repr. 1B Hazard Statements: Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction. May damage fertility.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

3-Aminomethyl-3,5,5-trimethylcyclohexylamine Trimethylhexane-1,6-diamine bisphenol A

Signal word:

Pictograms:



Hazard statements

| H314 | |
|-------|--|
| H317 | |
| H360F | |

Causes severe skin burns and eye damage. May cause an allergic skin reaction. May damage fertility.

Precautionary statements

Obtain special instructions before use.

P201



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B

| Revision date: 22.06.2017 | Product code: 00359-1009 | Page 2 of 9 |
|---------------------------|---|-------------|
| P202 | Do not handle until all safety precautions have been read and understood. | |
| P260 | Do not breathe vapour. | |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. | |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. | |
| P405 | Store locked up. | |
| | | |

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Hardener based on aliphatic polyamines

Hazardous components

| CAS No | Chemical name | | | Quantity |
|------------|---|------------------------------|--------------------------------|----------|
| | EC No | Index No | REACH No | |
| | Classification according to Regu | lation (EC) No. 1272/2008 [0 | CLP] | |
| 100-51-6 | Benzyl alcohol | | | < 20 % |
| | 202-859-9 | 603-057-00-5 | 01-2119492630-38 | |
| | Acute Tox. 4, Acute Tox. 4; H30 | 2 H332 | - | |
| 2855-13-2 | 3-Aminomethyl-3,5,5-trimethylcy | clohexylamine | | < 20 % |
| | 220-666-8 | 612-067-00-9 | 01-2119514687-32 | |
| | Acute Tox. 4, Acute Tox. 4, Skin H317 H412 | Corr. 1B, Skin Sens. 1, Aqua | atic Chronic 3; H302 H312 H314 | |
| 25620-58-0 | Trimethylhexane-1,6-diamine | | | < 5 % |
| | 247-134-8 | | 01-2119560598-25 | |
| | Acute Tox. 4, Skin Corr. 1A, Eye | Dam. 1, Skin Sens. 1A; H30 | 02 H314 H318 H317 | |
| 80-05-7 | bisphenol A | | | < 1 % |
| | 201-245-8 | 604-030-00-0 | 01-2119457856-23 | |
| | Repr. 1B, Eye Dam. 1, Skin Ser H411 | is. 1, STOT SE 3, Aquatic Cl | 1ronic 2; H360F H318 H317 H335 | |

Full text of H and EUH statements: see section 16.

Further Information

SVHC substance [Regulation (EC) No 1907/2006, Article 57]: bisphenol A

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. Call a physician immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B Product code: 00359-1009

Revision date: 22.06.2017

. . .

Page 3 of 9

In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water. Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Summon a doctor immediately.

After ingestion

Do not induce vomiting. Summon a doctor immediately. Induce vomiting only upon the advice of a physician. Attention. Beware, danger of aspiration.

4.2. Most important symptoms and effects, both acute and delayed

May damage fertility.

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

Additional information

Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal. Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B

Revision date: 22.06.2017

Product code: 00359-1009

Page 4 of 9

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Handle and open container with care. Handle in accordance with good industrial hygiene and safety practice. Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Advice on storage compatibility

Incompatible with: strong oxidizing agents strong acids and strong bases

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hard rubber surfacer

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|---------|-----------------------------|-----|-------|-----------|---------------|--------|
| 80-05-7 | Bisphenol A, inhalable dust | - | 10 | | TWA (8 h) | WEL |
| | | - | - | | STEL (15 min) | WEL |

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/



Test method

11

according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B

Revision date: 22.06.2017

Product code: 00359-1009

Page 5 of 9

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state: | Liquid |
|---|------------|
| Colour: | Yellowish |
| Odour: | Amine like |
| pH-Value (at 20 °C): Changes in the physical state | |

| Changes in the physical state | |
|--|--------------------|
| Initial boiling point and boiling range: | > 200 °C |
| Flash point: | 108 °C |
| Lower explosion limits: | n.d. |
| Upper explosion limits: | |
| Ignition temperature: | n.d. |
| Decomposition temperature: | > 200 °C |
| Vapour pressure: (at 20 °C) | 0,06 hPa |
| Density (at 25 °C): | 1,0 g/cm³ |
| Water solubility: | Partially miscible |
| Viscosity / dynamic: | 30 - 70 mPa⋅s |
| 2. Other information | |

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

oxidizing agents Acids and bases.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B

Revision date: 22.06.2017

Product code: 00359-1009

Page 6 of 9

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available.

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-Aminomethyl-3,5,5-trimethylcyclohexylamine; Trimethylhexane-1,6-diamine; bisphenol A)

Carcinogenic/mutagenic/toxic effects for reproduction

May damage fertility. (bisphenol A)

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

080409

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B

Revision date: 22.06.2017

Product code: 00359-1009

Page 7 of 9

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

| <u>14.1. UN number:</u> | UN 3267 |
|--|--|
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. |
| | (3-Aminomethyl-3,5,5-trimethylcyclohexylamine, |
| 14.2 Transport bazard alaga/aa) | Trimethylhexane-1,6-diamine) 8 |
| 14.3. Transport hazard class(es): | |
| <u>14.4. Packing group:</u> Hazard label: | 8 |
| Hazalu label. | 8 ^^ |
| | |
| | 8 |
| Classification code: | C7 |
| Limited quantity: | 5 L / 30 kg |
| Excepted quantity: | E1 |
| Transport category: | 3 |
| Hazard No: | 80 |
| Tunnel restriction code: | E |
| Inland waterways transport (ADN) | |
| <u>14.1. UN number:</u> | UN 3267 |
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. |
| | (3-Aminomethyl-3,5,5-trimethylcyclohexylamine, |
| | Trimethylhexane-1,6-diamine) |
| 14.3. Transport hazard class(es): | 8 |
| 14.4. Packing group: | III |
| Hazard label: | 8 |
| | |
| | |
| | |
| Classification code: | C7 |
| Limited quantity: | 5 L / 30 kg |
| Excepted quantity: | E1 |
| Marine transport (IMDG) | |
| <u>14.1. UN number:</u> | UN 3267 |
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Isophorondiamine and trimethylhexamethylene diamine) |
| 14.3. Transport hazard class(es): | 8 |
| 14.4. Packing group: | III |
| Hazard label: | 8 |
| | |
| | |
| | 8 |
| | |



according to Regulation (EC) No 1907/2006

| | TIP TOP REMAFIX L COMP. B | |
|--|--|-------------|
| Revision date: 22.06.2017 | Product code: 00359-1009 | Page 8 of 9 |
| Marine pollutant: | No | |
| Limited quantity: | 5 L / 30 kg | |
| Excepted quantity: EmS: | E1 F-A, S-B | |
| Air transport (ICAO-TI/IATA-DGR) | | |
| <u>14.1. UN number:</u> | UN 3267 | |
| 14.2. UN proper shipping name: | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Isophorondiamine and trimethylhexamethylene diamine, mixture) | I |
| 14.3. Transport hazard class(es): | 8 | |
| 14.4. Packing group: | III | |
| Hazard label: | 8 | |
| Limited quantity Passenger: Passenger LQ: | 1 L Y841 | |
| Excepted quantity: | E1 | |
| IATA-packing instructions - Passenger: | 852 | |
| IATA-max. quantity - Passenger: | 5 L | |
| IATA-packing instructions - Cargo: | 856 | |
| IATA-max. quantity - Cargo: | 60 L | |
| 14.5. Environmental hazards | | |
| ENVIRONMENTALLY HAZARDOUS: | no | |
| 14.6. Special precautions for user | atrial business and a fature attac | |
| Handle in accordance with good indu | | |
| 14.7. Transport in bulk according to Annex The transport takes place only in app | | |
| | | |
| SECTION 15: Regulatory information | | |
| 15.1. Safety, health and environmental reg | ulations/legislation specific for the substance or mixture | |
| EU regulatory information | | |
| Authorisations (REACH, annex XIV): Substances of very high concern, SV bisphenol A | HC (REACH, article 59): | |
| Restrictions on use (REACH, annex XVII Entry 66: bisphenol A |): | |
| 2004/42/EC (VOC): | 0 % | |
| National regulatory information | | |
| Employment restrictions: | Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. | |
| Water contaminating class (D): Additional information Consider Chemical prohibition regu | 2 - water contaminating | |
| 15.2. Chemical safety assessment | | |

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.



according to Regulation (EC) No 1907/2006

TIP TOP REMAFIX L COMP. B

Revision date: 22.06.2017

Product code: 00359-1009

Page 9 of 9

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
- IMDG = International Maritime Code for Dangerous Goods
- IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

| H302 | Harmful if swallowed. |
|-------|--|
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H360F | May damage fertility. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| | |

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)