



according to Regulation (EC) No 1907/2006

### **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

REMAFIX ST COMP. A

Art.-No.

525 1250, 525 1251

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Leveling compound

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50

Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

## Regulation (EC) No. 1272/2008

# Hazard components for labelling

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Formaldehyde, oligomeric reaction products with 1-chloro-2, 3-epoxypropane and phenol

Signal word: Warning

Pictograms:





### **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.



according to Regulation (EC) No 1907/2006

### **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 2 of 10

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P273 Avoid release to the environment.

P391 Collect spillage.

### Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

## 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a

PBT / vPvB substance.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### Chemical characterization

Mixture containing following substances with additives

### **Hazardous components**

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification according to Regulation (EC) No. 1272/2008 [CLP]					
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)					
	500-033-5	603-074-00-8	01-2119456619-26			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens.	1, Aquatic Chronic 2; H315 H319 H3	17 H411			
9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2, 3-epoxypropane and phenol					
	500-006-8		01-2119454392-40			
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411					

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

# General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

### After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

# After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

### After ingestion

Do not induce vomiting.

Drink plenty of water or milk.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.





according to Regulation (EC) No 1907/2006

### REMAFIX ST COMP. A

Revision date: 21.01.2019 Product code: 00359-1278 Page 3 of 10

# 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

Phenoles

### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

#### Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

## 6.2. Environmental precautions

Clean contaminated surface thoroughly.

Do not discharge into the drains/surface waters/ground water.

## 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

# 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

# Advice on safe handling

Keep container tightly closed.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

# Advice on protection against fire and explosion

No special protective measures against fire required.

## 7.2. Conditions for safe storage, including any incompatibilities





according to Regulation (EC) No 1907/2006

### **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 4 of 10

### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect against direct sun radiation.

Keep at temperatures between 3°C and 48°C.

## Hints on joint storage

Incompatible with:

Oxidizing agents

Amines

Acids and bases.

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Leveling compound

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1344-28-1	Aluminium oxides, inhalable dust	-	10		TWA (8 h)	WEL
1309-37-1	Rouge, total inhalable	-	10		TWA (8 h)	WEL
409-21-2	Silicon carbide (not whiskers), total inhalable	-	10		TWA (8 h)	WEL

## 8.2. Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

## Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

# Skin protection

Long sleeved clothing (DIN EN ISO 6530)

### Respiratory protection

No personal respiratory protective equipment normally required.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).



according to Regulation (EC) No 1907/2006

# **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 5 of 10

# **SECTION 9: Physical and chemical properties**

Solvent separation test:

Solvent content:

SECTION 9: Physical and chemical properties										
9.1. Information on basic physical and chemical properties										
Physical state:	pasty									
Colour:	Grey									
Odour:	Characteristic									
			Test method							
pH-Value:		n.d.								
Changes in the physical state										
Melting point:		n.d.								
Initial boiling point and boiling range:		n.d.								
Sublimation point:		n.d.								
Softening point:		n.d.								
Pour point:		n.d.								
Flash point:		> 100 °C								
Sustaining combustion:		Not sustaining combustion								
Flammability		Not sustaining combustion								
Solid:		n.a.								
Gas:		n.a.								
Explosive properties  The product is not explosive.										
Lower explosion limits:		n.d.								
Upper explosion limits:		n.d.								
Ignition temperature:		n.d.								
Auto-ignition temperature										
Solid:		n.a.								
Gas:		n.a.								
Decomposition temperature:		n.d.								
Oxidizing properties  Not oxidising.										
Vapour pressure:		n.d.								
Density (at 20 °C):		1,99 g/cm³								
Bulk density:		n.a.								
Water solubility: (at 20 °C)		Immiscible								
Solubility in other solvents										
Partition coefficient:		n.d.								
Viscosity / dynamic:		pasty								
Viscosity / kinematic:		n.d.								
Flow time:		n.d.								
Vapour density:		n.d.								
Evaporation rate:		n.d.								
Evaporation rate.		II.u.								

n.d.

n.d.





according to Regulation (EC) No 1907/2006

### **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 6 of 10

## 9.2. Other information

No data available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents Reactions with amines.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Protect against direct sun radiation.

# 10.5. Incompatible materials

Strong oxidizing agents

Amines

Acids and bases.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide phenol

## **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

### Sensitising effects

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700); Formaldehyde, oligomeric reaction products with 1-chloro-2, 3-epoxypropane and phenol)

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecological data are not available.



according to Regulation (EC) No 1907/2006

### REMAFIX ST COMP. A

Revision date: 21.01.2019 Product code: 00359-1278 Page 7 of 10

Toxic to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

Not readily biodegradable.

### 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

## 12.6. Other adverse effects

Hazardous water pollutant.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

### Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

### Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

**14.1. UN number:** UN 3082

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Classification code:

Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -



according to Regulation (EC) No 1907/2006

## **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 8 of 10

Inland waterways transport (ADN)

**14.1. UN number:** UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Epoxy resin)

9

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 9



Classification code: M6

Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es):

14.4. Packing group:
Hazard label: 9



Marine pollutant:

Limited quantity:

Excepted quantity:

EmS:

Yes

5 L / 30 kg

E1

E1

F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u> UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es):

14.4. Packing group:
Hazard label:
9



9

Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards





according to Regulation (EC) No 1907/2006

### **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 9 of 10

ENVIRONMENTALLY HAZARDOUS: yes



### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

2004/42/EC (VOC): < 5 %

Information according to 2012/18/EU E2 H

(SEVESO III):

E2 Hazardous to the Aquatic Environment

### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

### Changes

Changes in chapter:

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

## Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.



according to Regulation (EC) No 1907/2006

## **REMAFIX ST COMP. A**

Revision date: 21.01.2019 Product code: 00359-1278 Page 10 of 10

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)