

according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SOLUTION 12535 D

Art.-No.

536 6010, 538 1380

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name:	REMA TIP TOP AG
Street:	Gruber Strasse 65
Place:	D-85586 Poing
Telephone:	+49 (0) 8121 / 707 - 100
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de
1.4. Emergency telephone	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
number:	In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2 Aspiration hazard: Asp. Tox. 1 Skin corrosion/irritation: Skin Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Reproductive toxicity: Repr. 2 Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, > 5% n-hexane Colophonium

Signal word:

Danger

Pictograms:





according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 2 of 10

Hazard statements	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statemer	nts
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P260	Do not breathe vapour.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
	or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P273	Avoid release to the environment.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to in accordance with local and national regulations.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization Preparation in aliphatic hydrocarbons

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification	•		
92128-66-0	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, > 5% n-hexane			50 - 100 %
	924-168-8		01-2119472127-39	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361 H315 H336 H373 H304 H411			
8050-09-7	Colophonium			< 2,5 %
	232-475-7	650-015-00-7	01-2119480418-32	
	Skin Sens. 1; H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.



according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 3 of 10

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. If you feel unwell, seek medical advice.

After contact with skin

Wash off with soap and plenty of water. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting. Summon a doctor immediately. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. Causes skin irritation. May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

Additional information

Vapours are heavier than air and spread along ground. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Use only explosion-proof equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.



according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 4 of 10

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Inform competent authority about release into the sewage, ground or into waters.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Use only in thoroughly ventilated areas. Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Do not smoke - volatile. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
8050-09-7	Rosin-based solder flux fume	-	0.05		TWA (8 h)	WEL
		-	0.15		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours. Wash hands before breaks and immediately after handling the product.



according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 5 of 10

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Colourless	
Odour:	Hydrocarbon-like	
		Test method
pH-Value:	n.d.	
Changes in the physical state		
Melting point:	n.d.	
Initial boiling point and boiling range:	70 - 100 °C	
Sublimation point:	n.a.	
Softening point:	n.d.	
Flash point:	- 19 °C	
Flammability		
Solid:	n.a.	
Gas:	n.a.	
Explosive properties The product is considered non-explo	osive; nevertheless explosive vapour/air mixture can be	generated.
Lower explosion limits:	1,5 vol. %	•
Upper explosion limits:	7,5 vol. %	
Ignition temperature:	n.d.	
Auto-ignition temperature		
Solid:	n.a.	
Gas:	n.a.	
Decomposition temperature:	n.d.	
Oxidizing properties Not oxidising.		
Vapour pressure: (at 20 °C)	n.d.	



according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020	Product code: 00156-0438	Page 6 of 10
Density (at 15 °C):	< 1 g/cm³	
Bulk density:	n.a.	
Water solubility: (at 20 °C)	Immiscible	
Solubility in other solvents n.d.		
Partition coefficient:	n.d.	
Viscosity / dynamic:	n.d.	
Viscosity / kinematic: (at 40 °C)	< 20,5 mm²/s	
Flow time:	n.d.	
Vapour density:	n.d.	
Evaporation rate:	n.d.	
Solvent separation test:	0 %	
Solvent content:	> 95 %	
2. Other information		
No data available		

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive at intensive warming. Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known. Fire may produce: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available.

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, > 5% n-hexane LD50/oral/rat: > 5840 mg/kg LD50/dermal/rat: > 2920 mg/kg LC50/inhalation/rat: > 25200 mg/l/4 h



according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 7 of 10

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Colophonium)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility or the unborn child. (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, > 5% n-hexane)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, > 5% n-hexane)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, > 5% n-hexane)

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Hazard of lung oedema.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, > 5% n-hexane EC50/Algae/48 h = 10 - 30 mg/l

LC50/Oncorhynchus mykiss/96 h = 11,4 mg/l

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

<u>12.4. Mobility in soil</u>

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Severe hazard to waters.



according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 8 of 10

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133		
14.2. UN proper shipping name:	Adhesives		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3		
Classification code:	F1		
Limited quantity:	5 L / 30 kg		
Excepted quantity:	E2		
Transport category:	2		
Hazard No:	33		
Tunnel restriction code:	D/E		
Inland waterways transport (ADN)			
<u>14.1. UN number:</u>	UN 1133		
14.2. UN proper shipping name:	Adhesives		
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3		
Classification code:	F1		
Limited quantity:	5 L / 30 kg		
Excepted quantity:	E2		



according to Regulation (EC) No 1907/2006

SOLUTION 12535 D				
Revision date: 28.01.2020	Product code: 00156-0438	Page 9 of 10		
Marine transport (IMDG)				
<u>14.1. UN number:</u>	UN 1133			
14.2. UN proper shipping name:	Adhesives (Hydrocarbons, C6-C7, n-al hexane)	canes, isoalcanes, cyclics, > 5% n-		
14.3. Transport hazard class(es):	3			
14.4. Packing group:	II			
Hazard label:	3			
Marine pollutant:	Yes			
Limited quantity:	5 L / 30 kg			
Excepted quantity:	E2			
EmS:	F-E, S-D			
Air transport (ICAO-TI/IATA-DGR)				
<u>14.1. UN number:</u>	UN 1133			
14.2. UN proper shipping name:	Adhesives			
14.3. Transport hazard class(es):	3			
14.4. Packing group:	II			
Hazard label:	3			
Limited quantity Passenger:	1 L			
Passenger LQ:	Y341			
Excepted quantity:	E2			
IATA-packing instructions - Passenger:	353			
IATA-max. quantity - Passenger:	5 L			
IATA-packing instructions - Cargo:	364			
IATA-max. quantity - Cargo:	60 L			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	yes	¥2		

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
2004/42/EC (VOC):	> 95 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
Additional information:	E2

according to Regulation (EC) No 1907/2006

SOLUTION 12535 D

Revision date: 28.01.2020

Product code: 00156-0438

Page 10 of 10

National regulatory information

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

- CAS = Chemical Abstract Service
- EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)