

according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP SOLUTION T2-B

Art.-No.

517 7377, 517 7379 517 7390, 119000186

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name:	REMA TIP TOP AG
Street:	Gruber Strasse 65
Place:	D-85586 Poing
Telephone:	+49 (0) 8121 / 707 - 100
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de
<u>1.4. Emergency telephone</u> number:	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24 24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Germ cell mutagenicity: Muta. 2 Carcinogenicity: Carc. 1B Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Causes skin irritation. Causes serious eve irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. May cause cancer. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Trichloroethylene Zinc bis(dibutyldithiocarbamate)

nal word: Danger

Signal word:

Pictograms:





according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 2 of 11

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.
Precautionary sta	atements
P201	Obtain special instructions before use.

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P273	Avoid release to the environment.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with trichloroethylene

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to			
79-01-6	Trichloroethylene			< 85 %
	201-167-4	602-027-00-9	01-2119490731-36	
	Carc. 1B, Muta. 2, Skin Irr H341 H315 H319 H317 H			
1314-13-2	Zinc oxide			< 1 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic 0			
5459-93-8	N-Cyclohexyl-N-ethylamine			< 1 %
	226-733-8		01-2119949285-29	
	Flam. Liq. 3, Acute Tox. 3, H311 H332 H302 H314 H			
136-23-2	Zinc bis(dibutyldithiocarbamate)			< 1 %
	205-232-8	006-081-00-9	01-2119535161-51	
	Skin Irrit. 2, Eye Irrit. 2, Sk H319 H317 H335 H400 H			
793-24-8	N-1,3-dimethylbutyl-N'-phenyl-p-phenylenediamine			< 0,1 %
	212-344-0		01-2119485839-15	
	Acute Tox. 4, Skin Sens. 1			

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 3 of 11

Further Information

SVHC substance [Regulation (EC) No 1907/2006, Article 57]: Trichloroethylene

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Induce vomiting only upon the advice of a physician. Attention. Beware, danger of aspiration. Summon a doctor immediately. Immediately give plenty of water, if possible charcoal slurry.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of causing genetic defects. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray. Product does not burn, fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce: carbon monoxide and carbon dioxide Chlorine and traces of phosgene. Hydrogen chloride gas.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Keep away from heat and sources of ignition. Cool containers at risk with water spray jet.



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 4 of 11

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Care for thoroughly room ventilation, if necessary suck off at workplace. Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Incompatible with: Oxidizing agents Aluminium powder Alkaline metals and earth alkaline metals. Alkaline leaches

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 5 of 11

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1332-58-7	Kaolin respirable dust	-	2		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
79-01-6	Trichloroethylene	100	550		TWA (8 h)	WEL
		150	820		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Liquid Brown Sweetish	
		Test method
Changes in the physical state		
Initial boiling point and boiling range:	approx	. 90 °C
Flash point:		n.a. *)
Lower explosion limits:	7,9	vol. %
Upper explosion limits:		
Ignition temperature:		410 °C
Vapour pressure: (at 20 °C)		77 hPa
Density:	1,42	2 g/cm³



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017	Product code: 00156-0014	Page 6 of 11
Water solubility: (at 20 °C)	Immiscible	
Viscosity / dynamic:	2000 mPa·s	
Vapour density:	4,54	
Solvent content:	> 90 %	
0.0. Other information		

9.2. Other information

"*) According to PTB instructions, trichloroethylene has no flashpoint; however, vapour and air mixtures are flammable under a stronger energy influx."

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents. Reactions with alkalies. Reactions with alkali metals. Reactions with earth alkali metals.

10.4. Conditions to avoid

Above 120°C, a thermic decomposition may take place.

10.5. Incompatible materials

Alkaline metals and alkaline earth metals., Bases., oxidizing agents, Aluminium powder

10.6. Hazardous decomposition products

Chlorine and traces of phosgene. Hydrogen chloride gas Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available. Trichloroethylene LD50/oral/rat: 5400 mg/kg LD50/dermal/rabbit: > 2000 mg/kg LC50/inhalation/rat: 12500 ppm/4h

Irritation and corrosivity

Causes skin irritation. Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Trichloroethylene; Zinc bis(dibutyldithiocarbamate); N-1,3-dimethylbutyl-N'-phenyl-p-phenylenediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Trichloroethylene)

May cause cancer. (Trichloroethylene)

Reproductive toxicity: Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 7 of 11

STOT-single exposure

May cause drowsiness or dizziness. (Trichloroethylene)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Components of the product may be absorbed into the body through the skin. (skin absorption).

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Effects of breathing high concentrations of vapour may include:

Headache, dizziness, weakness, unconsciousness.

Hazard of lung oedema.

Skin contact or inhalation of solvents contained in this product may cause irritation of skin, eyes and mucous membranes.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available. Trichloroethylene LC50/Pimephales promelas/ 96 h = 42,4 mg/l EC50/Daphnia magna/48 h = 20,8 mg/l EC50/Algae/96 h = 36,5 mg/l Zinc oxide EC50/Selenastrum capricornutum/72 h = 0,17 mg/l Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Trichloroethylene Biodegradable (OECD): 2,4% (14 d) [OECD 301C] Not readily biodegradable.

12.3. Bioaccumulative potential

Trichloroethylene

Low bio-accumulation can be estimated because of low log Po/w. (Log Pow: 2,53)

12.4. Mobility in soil

Trichloroethylene High mobility in soil.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Severe hazard to waters

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 8 of 11

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1710
14.2. UN proper shipping name:	TRICHLOROETHYLENE, Solution
14.3. Transport hazard class(es):	6.1
14.4. Packing group:	111
Hazard label:	6.1
	6
Classification code:	T1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category: Hazard No:	2 60
Tunnel restriction code:	F
	E
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 1710
14.2. UN proper shipping name:	TRICHLOROETHYLENE, Solution
<u>14.3. Transport hazard class(es):</u>	6.1
14.4. Packing group:	III
Hazard label:	6.1
	6
Classification code:	T1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 1710
14.2. UN proper shipping name:	TRICHLOROETHYLENE SOLUTION
<u>14.3. Transport hazard class(es):</u>	6.1
14.4. Packing group:	III



according to Regulation (EC) No 1907/2006

	TIP TOP SOLUTION T2-B	
Revision date: 15.08.2017	Product code: 00156-0014	Page 9 of 11
Hazard label:	6.1	
Marine pollutant:	No	
Limited quantity:	5 L	
Excepted quantity:	E1	
EmS:	F-A, S-A	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1710	
14.2. UN proper shipping name:	TRICHLOROETHYLENE SOLUTION	
<u>14.3. Transport hazard class(es):</u>	6.1	
<u>14.4. Packing group:</u>	III	
Hazard label:	6.1	
	6	
Limited quantity Passenger:	2 L	
Passenger LQ: Excepted quantity:	Y642 E1	
IATA-packing instructions - Passenger:	655	
IATA-packing institucions - Passenger: IATA-max. quantity - Passenger:	60 L	
IATA-packing instructions - Cargo:	663	
IATA-max. quantity - Cargo:	220 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	
14.6. Special precautions for user		
Handle in accordance with good industr		
14.7. Transport in bulk according to Annex II		
The transport takes place only in appro		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regula	ations/legislation specific for the substance or mixture	
EU regulatory information		
Authorisations (REACH, annex XIV):		
Trichloroethylene		
Restrictions on use (REACH, annex XVII):		
Entry 28: Trichloroethylene		
2004/42/EC (VOC):	> 90 %	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juveni	le
-	work protection guideline' (94/33/EC). Observe employment restrictions	
	under the Maternity Protection Directive (92/85/EEC) for expectant or	
	nursing mothers.	
Water contaminating class (D).	3 - highly water contaminating	

Water contaminating class (D): 3 - highly water contaminating

Additional information

Consider Chemical prohibition regulation.



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 10 of 11

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm
- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

- vPvB = Very Persistent and very Bio-accumulative
- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration
- IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H350 May cause cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)



according to Regulation (EC) No 1907/2006

TIP TOP SOLUTION T2-B

Revision date: 15.08.2017

Product code: 00156-0014

Page 11 of 11

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)